

has holes which align with the horizontally aligned holes in the post, and a top cover moulding (17) is fitted to the post prior to attachment of the other display frame components.

Claim 61 (new) A display frame (1) as claimed in claim 60, wherein two sets of aligned holes (7) are provided in spaced relation, one above the other with a threaded rod or pin (9, 11) inserted and retained in each set of aligned holes.

#### REMARKS

Applicant has amended the application and submits that substantial care has been taken to avoid the introduction of any new subject matter into the application as a result of the foregoing amendments.


In particular, Applicant has cancelled claims 1-31 and added new claims 32-61. Applicant submits that the specification is replete with support for such claims. Thus, it is respectfully submitted that claims 32-61 introduce no new matter and are otherwise proper.

In light of the foregoing, Applicant respectfully submits that the Application is in *prima facie* condition for allowance at the present time. Accordingly, Applicant respectfully requests consideration of the present application and passage toward issuance thereof.

Respectfully submitted

KING & JOVANOVIĆ, PLC

Dated: 12/13/09

  
William L. King III  
Reg. No. 46,830

KING & JOVANOVIĆ, PLC  
170 College Avenue, Suite 230  
Holland, Michigan 49423  
Phone (616) 355-0400  
Facsimile (616) 355-9862